## **Carpentry & Building Construction**

# **Chapter 24 Brick Masonry & Siding**

### **Section 24.1 Assessment Answers**

- 1. the heel
- 2. Wear suitable eye protection. If cutting with a dry-cut masonry saw, wear a dust mask so as not to breathe in the fine brick dust.
- 3. by cleaning the mixing drum thoroughly after use and checking drive belts, the retractable guard, and the drive gears
- 4. All the dry ingredients should be measured and placed in the mixing drum and mixed for one minute before clean water is added.
- 5. Answers will vary.

### **Section 24.2 Assessment Answers**

- 1. A brick-veneer wall must be supported by a masonry or concrete foundation and be tied into the framework of the house.
- **2**. Wire-type ties are more corrosion resistant.
- 3. a partially constructed corner of brick
- **4**. To ensure that a course of brick is level and straight.
- 5.  $x = 7[(60 \times 9) + (60 \times 9) + (25 \times 9) + (25 \times 9)]$

#### **Section 24.3 Assessment Answers**

- 1. Makeup air replaces air exhausted by a combustion appliance.
- 2. The main parts of a fireplace include the fire-box, hearth, lintel and throat, damper, smoke shelf, and smoke chamber.
- 3. dimensions, height, shape, and interior smoothness
- 4. 2"
- 5. 1 1/16"